



GT-dMS2T

dMultiswitch®

Programmable Cascadable HYBRID dCSS® Multiswitch, 1 or 2 SAT with terrestrial Input, 32UB on 1 or 2 cable.



VIEW ONLINE



16, RUE MILLEWEE L-7257 HELMSANGE, WALFERDANGE, LUXEMBOURG

TEL +352 26 43 22 03 | FAX +352 26 43 22 04

info@gt-sat.com | www.gt-sat.com

TECHNICAL SPECIFICATIONS



INPUT FREQUENCY (SAT)	290 ~ 2350 MHz
INPUT FREQUENCY (TER)	40 ~ 862 MHz
OUTPUT FREQUENCY (SAT)	950 ~ 2150 MHz
OUTPUT FREQUENCY (TER)	40 ~ 862 MHz
INSERTION LOSS FOR SAT TRUNKS	3.5 dB (maximum)
INSERTION LOSS FOR TER TRUNKS	5.5 dB (maximum)
INSERTION LOSS FOR TER PATH	8.5 dB (maximum)
SAT INPUTS ISOLATION	20 dB (minimum)
MAXIMUM INPUT LEVEL (SAT)	-5 dBm
MAXIMUM INPUT LEVEL (TER)	0 dBm
OPERATING TEMPERATURE RANGE	0°C ~ +60°C
POWER SUPPLY	12V - 18V DC
POWER CONSUMPTION	4W (maximum) + LNB
ALL OUTPUTS	32
CONTROLLING	EN50494, EN50607, dHello
WORKING MODE	Dynamic and Static
PROGRAMMABILITY	YES
NUMBER OF OUTPUTS	2
LEGACY OUTPUTS	2 (switchable)
SYSTEM	1 or 3 satellites
COMMUNICATION PORT	Over coax cable
POWER SUPPLY UNIT	INCLUDED

PACKAGING INFORMATION

EAN CODE	5453001616315
----------	---------------

CONTACT US FOR MORE DETAILS.